

# (1)

# Portable Barrel & Tank Cleaning System

Easy in, easy out, fast thorough impingement cleaning!

## **AaquaBlaster LT**

AaquaTools AaquaBlaster LT portable barrel washing system is ideal for applications where the insertion opening is smaller than two inches such as wine barrels and closed head 55 gallon drums.

The cleaning efficiency of the AaquaBlaster LT is achieved thanks to four stream jets at low flow rate but high pressure, thus providing high impact washing. Stream nozzles rotate around a turret to provide complete orbital cleaning coverage of all interior surfaces.

The AaquaBlaster LT is driven by a hot or cold high pressure washer capable of producing 4 gallons per minute or higher of flow or more. The higher the flow the faster the rotation of the nozzles thus producing a more rapid cleaning cycle. High pressure inline Y filters are recommended and available to prevent particulates from interrupting the internal gears.

The AaquaBlaster LT is also available with quick change nozzles that will allow this unit to be used in tanks up to 10 feet tall.

### **Features**

- Rapid cleaning cycles with low flow rate
- Round, non-protruding washer head
- Two or four nozzle configuration
- Quick change nozzle configurations
- Inlet flows configurable
- Oversized gears, self-lubricating
- Small size

### **Benefits**

- Saves time, water and money
- Easy insertion
- Adaptable to barrel or tank cleaning
- Allows the tool to be used in tanks up to 10' tall
- Driven by nearly any hot or cold high pressure washer
- Smoother motion, withstands greater pressure and more durable
- Built for small openings like 55 gal drums or wine barrels for easy insertion

### **Specifications**

ClassRotating jet-headPowerPressure washer-drivenFlow Rate4-5.5 gpmTemperatureCold or hot up to 185°F (max)Pressure100-2000 psi (adjustable); 2300 psi (permissible)NozzlesBarrels 4 x 1/8" NPT, tanks 2 x 1/8" NPTSpray CoverageFour nozzle 6', two nozzle 10'Cleaning Cycle45 seconds and longerSpray Pattern360°Inlet ConnectionStandard ½" NPTInsertion Opening2" (max)LubricantSelf-lubricatingInstallationPortableMaterial316 Stainless Steel		
Flow Rate 4-5.5 gpm  Temperature Cold or hot up to 185°F (max)  Pressure 100-2000 psi (adjustable); 2300 psi (permissible)  Nozzles Barrels 4 x 1/8" NPT, tanks 2 x 1/8" NPT  Spray Coverage Four nozzle 6', two nozzle 10'  Cleaning Cycle 45 seconds and longer  Spray Pattern 360°  Inlet Connection Standard ½" NPT  Insertion Opening 2" (max)  Lubricant Self-lubricating  Installation Portable  Material 316 Stainless Steel	Class	Rotating jet-head
Temperature Cold or hot up to 185°F (max)  Pressure 100-2000 psi (adjustable); 2300 psi (permissible)  Nozzles Barrels 4 x 1/8" NPT, tanks 2 x 1/8" NPT  Spray Coverage Four nozzle 6', two nozzle 10'  Cleaning Cycle 45 seconds and longer  Spray Pattern 360°  Inlet Connection Standard ½" NPT  Insertion Opening 2" (max)  Lubricant Self-lubricating  Installation Portable  Material 316 Stainless Steel	Power	Pressure washer-driven
Pressure 100-2000 psi (adjustable); 2300 psi (permissible)  Nozzles Barrels 4 x 1/8" NPT, tanks 2 x 1/8" NPT  Spray Coverage Four nozzle 6', two nozzle 10'  Cleaning Cycle 45 seconds and longer  Spray Pattern 360°  Inlet Connection Standard ½" NPT  Insertion Opening 2" (max)  Lubricant Self-lubricating  Installation Portable  Material 316 Stainless Steel	Flow Rate	4-5.5 gpm
Nozzles Barrels 4 x 1/8" NPT, tanks 2 x 1/8" NPT  Spray Coverage Four nozzle 6', two nozzle 10'  Cleaning Cycle 45 seconds and longer  Spray Pattern 360°  Inlet Connection Standard ½" NPT  Insertion Opening 2" (max)  Lubricant Self-lubricating  Installation Portable  Material 316 Stainless Steel	Temperature	Cold or hot up to 185°F (max)
Spray Coverage Four nozzle 6', two nozzle 10' Cleaning Cycle 45 seconds and longer Spray Pattern 360° Inlet Connection Standard ½" NPT Insertion Opening 2" (max) Lubricant Self-lubricating Installation Portable Material 316 Stainless Steel	Pressure	100-2000 psi (adjustable); 2300 psi (permissible)
Cleaning Cycle 45 seconds and longer  Spray Pattern 360°  Inlet Connection Standard ½" NPT  Insertion Opening 2" (max)  Lubricant Self-lubricating  Installation Portable  Material 316 Stainless Steel	Nozzles	Barrels 4 x 1/8" NPT, tanks 2 x 1/8" NPT
Spray Pattern 360° Inlet Connection Standard ½" NPT Insertion Opening 2" (max) Lubricant Self-lubricating Installation Portable Material 316 Stainless Steel	Spray Coverage	Four nozzle 6', two nozzle 10'
Inlet Connection Standard ½" NPT Insertion Opening 2" (max) Lubricant Self-lubricating Installation Portable Material 316 Stainless Steel	Cleaning Cycle	45 seconds and longer
Insertion Opening 2" (max)  Lubricant Self-lubricating Installation Portable  Material 316 Stainless Steel	Spray Pattern	360°
LubricantSelf-lubricatingInstallationPortableMaterial316 Stainless Steel	Inlet Connection	Standard ½" NPT
Installation Portable  Material 316 Stainless Steel	Insertion Opening	2" (max)
Material 316 Stainless Steel	Lubricant	Self-lubricating
	Installation	Portable
Weight 9 lbs	Material	316 Stainless Steel
weight o lus	Weight	8 lbs
Warranty One year limited warranty	Warranty	One year limited warranty

### **Ordering Information**

AaquaBlasterLT	AaquaBlaster LT, 2 or four nozzle system (nozzle head only)
AaquaBlasterLT/stand	AaquaBlaster LT and stand
HotCart	HotCart hot high pressure washer
107146814	KEW Poseidon 7-67 cold & hot water pressure washer
WBW/Power-Coated	Mounting rack, 2 or 4 wine barrel platform
ANT4C	Hydro Twister® 4-in-1 surface cleaner

### **Applications**

Barrel washing, tank washing, tote/IBC cleaning, storage tank washing, fuel tank cleaning.

### **Special Features**



The AaquaBlaster LT incorporates a stand at the base that stabilizes and protects the cleaning device during and after insertion. The AaquaBlaster LT allows for easy insertion into wine barrels mounted on most Western Square or TOPCO type barrel pallets and can be incorporated into the Western Square barrel cleaning platform that contains rollers for easy rotation.



Oversized case and gears provide a significant advantage over the competition, smoother motion and withstands greater pressure. The gears are made from a revolutionary self-lubricating hard plastic that is more durable than brass.

### **Compatible Products**

**HotCart Hot High Pressure Washer –** Just provide the water and we'll heat it up to 185°F with flows up to 13.2 gallons per minute. With AaquaTools HotCart hot high pressure washer option, you can enjoy hot water and high pressure up to 2750 psi with flows up to 5.5 gpm.





Poseidon Hot & Cold High Pressure Washer – The KEW Poseidon 7-67 premium class industrial cold & hot (up to 185°F) water pressure washer combines the renowned lifetime and quality of the C3 pump with optimal ergonomics to bring an unbeatable heavy duty pressure washer to many industries. The high water flow makes it very useful for applications where a high level of dirt has to be removed or flushed away.

**Mounting Racks –** For easy insertion we offer a variety of storage and mounting racks. Our traditional 2 or 4 barrel pallet wash platform removes any need for heavy lifting when inserting our container cleaner.





P/N AaquaBlaster-LT\_V1 - 05/13

© 2013 AaquaTools, Inc. – All rights reserved.

Specifications are subject to change without notice.

### AaquaTools, Inc.

3233 Fitzgerald Road, Ste. B Rancho Cordova, CA 95742

Toll-free: 800.777.2922 Direct: 916.635.2922 Fax: 916.635.8856 info@aaquatools.com www.aaquatools.com